

## A-F-CON



### DESCRIZIONE/DESCRIPTION

Contatori lancia impulsi flangiati.  
Flanged pulse emitter meter.




### CARATTERISTICHE TECNICHE/TECHNICAL FEATURES

Calibro - Size - DN Gauge - Size - DN	mm	50	65	80	100	125	150	200	
Portata massima Qmax (CEE) Qmax max. flow rate (CEE)	m <sup>3</sup> /h	50	80	200	250	250	450	650	
Portata nominale QN (CEE) QN Nominal flow rate (CEE)	m <sup>3</sup> /h	30	50	80	120	120	300	500	
Portata Minima Qmin (CEE) Minimun Flow Qmin (CEE)	m <sup>3</sup> /h	0,35	0,40	1	1,2	1,2	2,5	4	
Massima temperatura dell'acqua Max Working Temperature	°C	40	40	40	40	40	40	40	
Massima pressione di lavoro Max Working Pressure	BAR	16	16	16	16	16	16	16	
Volumi disponibili per impulso Volumes for pulse available	Impulsi/lt Pulse/lt	1/100	1/100	1/100	1/100	1/100	1/1000	1/1000	
Modelli disponibili (k=litri per impulso) Avaible models (k=liter per pulse)	Flange	2"	2"1/2	3"	4"	5"	6"	8"	
	STD.	1 Imp/100l (k=100) 1 Pul/100l (k=100)					1 Imp/1000l (k=1000) 1 Pul/1000l (k=1000)		



### DIMENSIONI/DIMENSIONS



Codice Code	Modello Model	Flange	DN	Qn	PN	L	h	H	Price (€)
		mm	mm	m <sup>3</sup>		mm	mm	mm	
ADCONFC05	A-CON/C 2	2"	50	15	16	200	75	125	
ADCONFC06	A-CON/C 2 1/2	2"1/2	65	25	16	200	83	126	
ADCONFC07	A-CON/C 3	3"	80	40	16	225	95	172	
ADCONFC08	A-CON/C 4	4"	100	60	16	250	105	172	
ADCONFC09	A-CON/C 5	5"	125	60	16	250	120	172	
ADCONFC10	A-CON/C 6	6"	150	150	16	300	135	172	
ADCONFC11	A-CON/C 8	8"	200	250	16	350	160	201	

Codice Code	Modello Model	Connettore Connector	Ingresso-Uscita In-Out	Impulsi Pulses	Portata nom. Flow-rate nom.	Price (€)
					m <sup>3</sup> /h	
ADCONFC05	Connettore flangiato Threaded water meter	HIRSCHMANN	Flange 2"	1 IMP/lt 100 lt	30	
ADCONFC050B	Connettore flangiato Threaded water meter	BNC	Flange 2"	1 IMP/lt 100 lt	30	
ADCONFC06	Connettore flangiato Threaded water meter	HIRSCHMANN	Flange 2" 1/2	1 IMP/lt 100 lt	50	
ADCONFC060B	Connettore flangiato Threaded water meter	BNC	Flange 2" 1/2	1 IMP/lt 100 lt	50	
ADCONFC07	Connettore flangiato Threaded water meter	HIRSCHMANN	Flange 3"	1 IMP/lt 100 lt	80	
ADCONFC070B	Connettore flangiato Threaded water meter	BNC	Flange 3"	1 IMP/lt 100 lt	80	
ADCONFC08	Connettore flangiato Threaded water meter	HIRSCHMANN	Flange 4"	1 IMP/lt 100 lt	120	
ADCONFC080B	Connettore flangiato Threaded water meter	BNC	Flange 4"	1 IMP/lt 100 lt	120	
ADCONFC09	Connettore flangiato Threaded water meter	HIRSCHMANN	Flange 5"	1 IMP/lt 100 lt	120	
ADCONFC090B	Connettore flangiato Threaded water meter	BNC	Flange 5"	1 IMP/lt 100 lt	120	
ADCONFC10	Connettore flangiato Threaded water meter	HIRSCHMANN	Flange 6"	1 IMP/lt 100 lt	300	
ADCONFC100B	Connettore flangiato Threaded water meter	BNC	Flange 6"	1 IMP/lt 100 lt	300	
ADCONFC11	Connettore flangiato Threaded water meter	HIRSCHMANN	Flange 8"	1 IMP/lt 100 lt	500	
ADCONFC110B	Connettore flangiato Threaded water meter	BNC	Flange 8"	1 IMP/lt 100 lt	500	