

CONDUIT



Passante a muro ABS per bocchetta 2"1/2F-1"1/2F | 250mm

ABS wall-through pipe for nozzle
2"1/2F-1"1/2F | 250mm



Passante a muro ABS per bocchetta 2"1/2F-1"1/2F | 300mm

ABS wall-through pipe for nozzle
2"1/2F-1"1/2F | 300mm



CAMPO DI UTILIZZO

Piscine pubbliche e private con strutture in cemento per bocchette con rivestimento in PVC e Piastrelle
Tecnologia a Skimmer con strutture in cemento per bocchette con rivestimento in PVC e Piastrelle
Tecnologia a bordo sfioratore con strutture in cemento per bocchette con rivestimento in PVC e Piastrelle



CONTEXT OF USE

Public and private pools with concrete structures for nozzles with PVC lining and Tiles
Skimmer technology with concrete structures for nozzles with PVC lining and Tiles
Overflow edge technology with concrete structures for nozzles with PVC lining and Tiles



DESCRIZIONE

Corpo in ABS con alloggiamento bocchetta 2"1/2 F -1"1/2 F
Tappi di protezione filetti (pz°2)



DESCRIPTION

ABS body with nozzle housing 2"1/2 F -1"1/2 F
Thread protection caps (2 pcs)



CARATTERISTICHE TECNICHE

Portata alla velocità massima di immissione di 4 m/s 14,03 m³/h



TECHNICAL FEATURES

Flow rate at maximum inlet speed of 4 m/s 14.03 cu. m/h

Codice/Code	Descrizione/Description	Pack	Weight	Unit	Price (€)
200200686	Passante a muro ABS per bocchetta 2"1/2F-1"1/2F 250mm ABS wall-through pipe for nozzle 2"1/2F-1"1/2F 250mm	1	0.50 Kg	NR	
200200685	Passante a muro ABS per bocchetta 2"1/2F-1"1/2F 300mm ABS wall-through pipe for nozzle 2"1/2F-1"1/2F 300mm	1	0.60 Kg	NR	

